



Make It Yours.

ELITE NEX WHITE W700

MPW-7001-ACAW-B

NEX LEVEL POWER



FEATURES

Active power factor correction and a dual forward topology design: Constructed with protective measures normally only found in high-end power supplies that improve overall safety and current stability.

Excellent temperature resistance: Capable of comfortably operating at 40°C under full loads, allowing for a longer lifespan even in warmer environments.

High peak power tolerance: Can reliably push an additional 100W at peak power loads for up to 20 seconds.

80 Plus White efficiency: Maintains an efficiency of 80% at typical loads.

Durable, reliable, and safe: Will perform consistently in any environment, whether you live at high altitudes or in high humidity.

3-year warranty: This unit comes with a standard limited manufacturing warranty of 3 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
US	4719512130636	884102102950
EU	4719512130643	884102102967
TW	4719512130650	884102102974
BR	4719512130667	884102102981
JP	4719512130674	884102102998
WO	4719512130681	884102103001
BU	4719512130698	884102103018
BS	4719512130704	884102103025
CP	4719512130711	884102103032

Net Weight	1.59 kg / 3.505 lb
Gross Weight	1.97 kg / 4.343 lb
Package Dimensions	245 x 190 x 95mm (9.65 x 7.48 x 3.74")
Carton Dimensions	503 x 260 x 220mm (19.8 x 10.24 x 8.66")
Unit / Carton	5 pcs
Carton / Pallet	64 pcs

The ELITE NEX White is the dependable choice for entry level builders looking for a strong, reliable PSU. The quiet 120mm fan, active power factor correction, exceptional temperature resistance, high peak power tolerance, excellent efficiency, overall durability, and 3-year warranty deliver a complete package of a PSU that gives you everything you need. The ELITE NEX White has been engineered for outstanding but accessible reliability, performance, and stability.

SPECIFICATIONS

Product Name	ELITE NEX White W700	
Item Code	MPW-7001-ACAW-B	
ATX Version	ATX12V Rev. 2.41	
PFC	Active PFC	
Input Voltage	100 - 240V	
Input Current	10A	
Input Frequency	47 - 63Hz	
Dimensions (L x W x H)	140 x 150 x 86mm	
Fan Size	120mm	
Fan Bearing	Sleeve Fan	
Efficiency	≥ 80% @ Typical Load	
ErP 2014 Lot 3	Yes	
Operating Temperature	0 - 40°C	
Power Good Signal	100 - 500 ms	
Hold Up Time	≥ 10ms at 100% Load	
MTBF	> 100,000 hours	
Protections	OVP / OPP / UVP / OTP / SCP / Surge & Inrush Protection	
Regulatory	TUV,cTUVus,CE,FCC,BSMI,CCC,EAC,UKCA	
Connectors	ATX 24 Pin	x1 = 1x (550mm)
	EPS 4+4 Pin / EPS 8 Pin	x1 = 1x (550+120mm)
	PCI-e 6+2 Pin	x2 = 1x (500+120mm)
	SATA	x2 = 1x (400+120mm); x3 = 1x (400+120+120mm)
	Peripheral 4 Pin	x3 = 1x (400+120+120mm)

AC INPUT	100 - 240V~, 10A, 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	17A	19A	54A	0.3A	2.5A
TOTAL POWER	110W		648W	3.6W	12.5W
	700W				